



Ereliable Lithium Bateries

MSDS REPORT

SECTION 1 – Product and Company Identif acation

Product Name:	Lithium Iron Phosphate LiFePO4 Batery
Model:	ER-12V100A1
EAN Code:	4270002748408
Brand:	EREL
Specificaaon:	1280Wh, 100Ah, 12,8V
Weight:	11 Kg
Dimensions:	307 x 169 x 208mm (LxWxH)
Manufacturer:	Ereliable, Lukas Schaarschmidt
Address:	Auf der Horst Süd 13, 21255 Kakenstorf, Germany
Contact Person:	Lukas Schaarschmidt
Phone:	+49 4186 24 73 29 3
E-Mail:	info@ereliable.de
Emergency Tel:	+49 173 7530 599

SECTION 2 – Hazards Idendificaation

Classificaatn of Danger:	See secton 14.
Primary Route(s) of Exposure:	Eye, skin contact, ingestio
Health Hazard:	The bateries are not hazardous when used according to the instructions of manufacturer under normal ccondions. In case of abuse, there's Hazard of rupture, fire, heat, leakage of internal components, which could cause casualty loss. Abuses including but not limited to the following cases: charged for long tions e, short circuited, put into fire, whacked with hard object, punctured with acute object, crushed, and broken.



Ereliable Lithium Bateries

Chemical Name	Concentraton (%)	CAS Number
Iron Lithium Phosphate (LiFePO4)	20 - 40	15365-14-7
Graphite	10 - 20	7782-42-5
Phosphate(1-), hexafluoro-, lithium	10 - 20	21324-40-3
Aluminum Foils	5 - 10	7429-90-5
Copper Foils	1 - 10	7440-50-8
Nickel	1 - 5	7440-02-0
Other	1 - 5	N/A

SECTION 3 – Compostion / Informationon Ingredients

Labeling according to EC directves. No symbol and Hazard phrase are required. Note: CAS number is Chemical Abstract Service Registry Number. N/A=Not apply

SECTION 4 – First Aid Measures

Eye contact	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin contact	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingesti n	Give at least 2 glasses of milk or water. Induce vomiting u less paati t is unconscious. Call a physician.

SECTION 5 – Fire Fighting Measues

Characteristcs of Hazard	Dusts at sufficient concentrarationan form explosive mixtures with air. Combustion enerates toxic fumes.
Hazardous Combustio Products	Carbon dioxide.
Fire-exting ishing Methods and Extingushing Media	For small fires, use water spray, dry chemical, carbon dioxide or chemical foam.
Attenti in Fire- extingui hing	Wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protectiegear.

MATERIAL SAFETY DATASHEET



Ereliable Lithium Bateries

SECTION 6 – Accidental Release Measures

Personal Precautio s, protectve equipment, and emergency procedures	In case of rupture. Atenntion! Coosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventil aon. Use personal protective eq ipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protectve measures listed in Secti ns 7 and 8.
Environmental Precautons	Prevent product from contaminatin soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Secon 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

SECTION 7 – Handling and Storage

Handling	The batery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.
Storage	Store in a cool, dry, well-ventil ted area away from incompaatle substances. Store locked up. Keep out of the reach of children.
Other Precautio s	In case of rupture. Handle in accordance with good industrial hygiene and safety practie. Avoid contact with skin, eyes or cloth ing. Use personal protecton equipment.

SECTION 8 – Exposure Controls / Personal Protection

Engineering Controls	Use adequate ventila on to keep airborne concentrarons low. If used under conditons that generate pparculates, the ACGIH TLV -TWA of 3mg/m3 respirable fracton (10mg/m3 total) should be observed.
Personal Protectve Equipment	 Eye and Face Protecti n: None required for consumer use. If there is a Hazard of contact: Tight sealing safety goggles. Face protection shield. Skin and Body Protecti n: None required for consumer use. If there is a Hazard of contact: Wear protecti e gloves and prottective oth ing.
	Respiratory Protecton : No protectve equipment is needed under normal use conditons. If exposure limits are exceeded or irritaations experienced, ventila on and evacuauan may be required.

MATERIAL SAFETY DATASHEET



Ereliable Lithium Bateries

SECTION 9 – Physical and Chemical Properties

Physical State	Appearance: Prismatic
	Color: Black
	Odour: If leaking, smells of medical ether.

Change in condition

рН	Not applicable as supplied.
Flash Point	Not applicable unless individual components exposed.
Flammability	Not applicable unless individual components exposed.
Relatve density	Not applicable unless individual components exposed.
Solubility (water)	Not applicable unless individual components exposed.
Solubility (other)	Not applicable unless individual components exposed.

SECTION 10 – Stability and Reactivity

Chemical Stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactons	None under normal processing.
Conditons to Avoid	Exposure to air or moisture over prolonged periods.
Incompati le materials	Acids, Oxidizing agents, Bases.
Hazardous Decompositon Products	Carbon oxides.

SECTION 11 – Toxicological Information

Irritaton	In the event of exposure to internal contents, vapour fumes may be very irritatig to the eyes and skin.
Sensitizat n	Not Available.
Reproductive T xicity	Not Available.
Toxicologically Synergistc Materials	Not Available.





Ereliable Lithium Bateries

SECTION 12 – Ecological Information

General note	Do not allow undiluted product or large quanties of it to reach ground water, water course or sewage system.
Antcipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity	Not Available.

SECTION 13 – Disposal Considerations

Waste Treatment	Recycle or dispose of in accordance with government, state & local regulati ns.
Attenti for Waste Treatment	Deserted bateries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.

SECTION 14 – Transport Information

UN number	3480
Proper shipping name	Lithium ion bateries (limited to a maximum of 30% SoC)
Class or division	9
Label(s) / Placard Required	Miscellaneous Lithium batt

Special precautons which a user needs to be aware of, or needs to comply with, in connnecon with transport or conveyance either within or outside their premises

icao / Iata	Can be shipped by air in accordance with Internatio al Civil Aviaati Organizatio (ICAO), TI or Internaati al Air Transport Associaion (IATA), DGR Packing Instruction (PI) 965 SeectionA appropriate of IATA DGR 60th (2019 Editio) for transporttat n.
IMDG CODE	Shipping may be done in accordance with the IMDG Code 2018 Edition (Amdt 39-18).
DOT	Other requirements for the US Department of Transportati n (DOT) Subchapter C, Hazardous Materials Regulatio s if shipped in compliance with 49 CFR 173.185.
ADR/ ADN	Transport Requirements for United Natio s Economic Commission for Europe (UNECE) ADR/ADN, Applicable as from 1 January 2019

Each batery of the type declared in this document is proved to meet the requirements of each applicable test in the UN Manual of Tests and Criteria, Part III, Secti n 38.3

MATERIAL SAFETY DATASHEET



Ereliable Lithium Bateries

SECTION 15 – Regulatory Information

- Dangerous Goods Regulatons
- Recommendatons on the Transport of Dangerous Goods -Model Regulatons (20th revised edition)
- Recommendatons on the Transport of Dangerous Goods -Manual of Tests and Criteria
- Internati nal Air Transport Associaaon (IATA)
- Internati nal Mariime Dangerous Goods (IMDG Code 2018 Edidin Amdt 39 -18)
- Technical Instruction for the Safe Transport of Dangerous Goods
- Classificaaon and code of dangerous goods (GB 6944-2012)
- 2012 OSHA Hazard Communicati n Standard (29 CFR 1910.1200)
- Toxic Substance Control Act (TSCA)
- Code of Federal Regulatio s
- In accordance with all Federal, State and local laws

SECTION 16 – Additional Information

Avoid any mechanical or electrical abuse of the Lithium Iron Phosphate batery. Use and Install the batter accordance with the insstrucon manual.

Disclaimer: To the best of our knowledge, the informaton contained herein is accurate. However, neither the abovenamed supplier nor any of its subsidiaries assumes any liability whatsever for the accuracy or completeness of the information of contained herein. Final determinaat of suitability of any material is the sole responsibility of the user. All material s may present unknown hazards and should be used with cauton. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist

END OF REPORT